

Version 1.0

Updated 21 Jan 2021

The Professionals	s' Choice	Updated 21 Jan 2021
	Arborist	t 200P
	Description	Notes
Basics	Weight	1270Kgs
	Max Timber Diameter	200mm
	Throughput	22 Cubic Metres per hour 7 tonnes per hour
	Fuel Tank Capacity	27 Litres - More than enough for a days work
	Hydraulic Oil Tank Capacity	27 Litres - Fitted with sight gauge and filter
Engine	Make & Model	Kubota / 57hp
	Cubic Capacity	1537cc
	Fuel	Petrol
	Cylinders	4
	Turbo	No
	Cooling	Water cooled
	Torque (Nm)	120 @ 2400RPM
	Throttle Control	Electronic
	Main Drive Belt Tensioning	Manual with clutch system
	Engine Bay Heat Management	Heat Transfer Fan (Patent Pending)
	Engine Cover/Bonnet	Hinged steel construction
		Lined with sound reduction material
		Lockable
	Clutch	Yes
	Power Feed Rollers	2
Спиринд	1 ower recurrences	Hydraulically driven by a motor on each roller
	Disc Processor/ Flywheel	93Kgs
	Disc Blade Cutters	4 cutters
	Disc Blade Catters	720-900 Hours expected life on clean material
	Main Drive Shaft Bearings	Oversized / greaseable
	Infeed Chute Aperture (W X H)	1200mm x 840mm
	Infeed Throat Aperture (W x H)	200mm x 280mm
	Sound Pressure LPA	92 dB(A
	Sound Power LWA	115 dB(A)
0 1 1		
Controls	Roller Control Buttons	2 x Banks of 3 buttons located each side of the
		Infeed chute:
		1 x Button for forward the rollers 1 x Button for reverse of the rollers
		1 x Button for the entire rollers 1 x Button for throttle reset
	Throttle Control	N/A
Cofoty	Safety Bars	EN 13525 Compliant
Safety	Salety Bais	Floating to equalize pressure at all points
		Built in sections to remove cost of replacement
	Top Safety Button	EN 13525 Compliant
	' '	Located on top of the infeed chute
Discharge	Discharge Chute	Rotation of 280° to safeguard the operator
		Adjustable end cap to direct material
Draw Bar	Adjustable A Frame Design	50mm ball coupling as standard. See Options:
	- tay account of the same of the same	Adjustable to suit various vehicles
		Hand brake
	Electric Cable	Removable spiral cable for safe stowage
		13 pin plug to comply with European rules
Axle	ALKO	Fully braked system which includes:
	7.2.0	Over-run braking and hand brake
Dimensions	Longth Transport	
Dimensions:	Length Transport	3990mm
	Width Transport	1440mm
	Height Discharge Chute Up	2695mm
		L and FCL Ocean Freight, please ask for details.
Optional Equipment:		Standard RAL colours only
	Adjustable Swan Neck Hitch	Ball or eye hitch