

SAFELIFT®

 Made in Sweden

MAST LIFTS FOR INDOOR USE



Mast lifts for indoor use

Safelift is a series of compact and flexible mast lifts for working safely indoors. Our lifts are characterised by low entry, short turning radius and low weight.

Safelift makes work at height efficient and safe, eliminating the need for ladders.

Our lifts are manufactured in Sweden and are CE marked in accordance with the high standards of safety in the EC and EN280 standards.



Areas of use

Safelift's products are developed to facilitate work in, for example, trade, installation, cleaning, property upkeep, warehouse and construction industry.

All our products are easy to use and maintain. All lifts are delivered assembled and ready to start. At the end of the working day, the lift is connected to a standard wall outlet and the built-in charger charges the batteries.

It hardly becomes any smoother than that.

- ✓ **SMOOTH**
- ✓ **SAFE**
- ✓ **SMART**

**EFFICIENT
MAST LIFTS FOR
INDOOR USE**

Safelift's mast lifts are approved
in accordance with SS-EN-280





EASY TO USE

STABLE CONSTRUCTION

LOW DEAD WEIGHT

OUR PRODUCTS

Safelift is produced in three different models

PushAround, MoveAround & StockPicker, the models are manufactured with a working height from 3.5 to 6.0 m. Safelift's mast lifts are safe and easy to use and require minimal maintenance. The lifts are delivered on EU pallets, ready for use. At the end of the working day, the lift is connected to a standard wall outlet and the built-in charger charges the batteries.

Visit www.safelift.se/en for further information.




PushAround

Manually moved to where it's needed.




MoveAround

Operated with a joystick from the basket.



StockPicker

Drivable and has a height-adjustable lifting table.





3.5M
WORKING HEIGHT

130KG
MAX LOAD

236KG
WEIGHT



PushAround
PA35

Manually movable small and flexible lift with 3.5 meters working height. Suitable for properties with low ceilings and without the requirement for mobility in an elevated position.

SPECIFICATIONS

Size of the platform	0.55 m × 0.65 m
Total load on the platform	Max 130 kg
Total number of people	Max 1
Working height	3.5 m
Platform height	1.5 m
Lifting time (130 kg)	14.5 s
Weight	236 kg
Total width	0.7 m
Total height	1.6 m
Total length	1.0 m
Power source	2 pcs 12V batteries, 9Ah, maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Electric motor, 24V DC
Wheels	ø 160 mm (front) / 125 mm (rear), polyurethane coating, leaves no marks
Parking brakes	Automatic (front), Manual (rear)
Height of railing	1.1 m
Height of skirting board	0.15 m



**PushAround
PA50**

Manually movable stylish and flexible lift with 5 meters working height. Suitable for properties with high ceilings and without the requirement for mobility in an elevated position.

SPECIFICATIONS

Size of the platform	0.53 m × 0.76 m
Total load on the platform	Max 180 kg
Total number of people	Max 1
Working height	5 m
Platform height	3 m
Lifting time (180 kg)	16 s
Weight	331 kg
Total width	0.76 m
Total height	1.66 m
Total length	1.16 m
Power source	2 pcs 12V batteries, 80Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Manual
Height of railing	1.1 m
Height of skirting board	0.15 m



**5M
WORKING HEIGHT**

**180KG
MAX LOAD**

**331KG
WEIGHT**



6M
WORKING HEIGHT

180KG
MAX LOAD

466KG
WEIGHT



MoveAround
PA60

Manually movable stylish and flexible lift with 6 meters working height. Suitable for properties with high ceilings and without the requirement for mobility in an elevated position.

SPECIFICATIONS

Size of the platform	0.53 m x 0.76 m
Total load on the platform	Max 180 kg
Total number of people	Max 1
Working height	6 m
Platform height	4 m
Lifting time (150 kg)	18.5 s
Weight	466 kg
Total width	0.76 m
Total height	1.98 m
Total length	1.16 m
Power source	2 pcs 12V batteries, 80Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Automatic
Height of railing	1.1 m
Height of skirting board	0.16 m



**MoveAround
MA50**

Driveable lift with a working height of 5 meters that can be disengaged for manual movement in narrow passages. Suitable for properties with high ceilings and requirements for mobility in an elevated position.

SPECIFICATIONS

Size of the platform	0.53 m x 0.76 m
Total load on the platform	Max 180 kg
Total number of people	Max 1
Working height	5 m
Platform height	3 m
Lifting time (180 kg)	16 s
Weight	331 kg
Total width	0.76 m
Total height	1.66 m
Total length	1.16 m
Driving speed	Lowered 4 km/h, raised 2 km/h
Power source	2 pcs 12V batteries, 80Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Automatic
Height of railing	1.1 m
Height of skirting board	0.15 m



5M
WORKING HEIGHT

180KG
MAX LOAD

331KG
WEIGHT

SAFELIFT®



6M
WORKING HEIGHT

180KG
MAX LOAD

466KG
WEIGHT



MoveAround
MA60

Driveable lift with a working height of 6 meters that can be disengaged for manual movement in narrow passages. Suitable for properties with extra high ceilings and demands for mobility in an elevated position.

SPECIFICATIONS

Size of the platform	0.53 m × 0.76 m
Total load on the platform	Max 180 kg
Total number of people	Max 1
Working height	6 m
Platform height	4 m
Lifting time (180 kg)	18.5 s
Weight	466 kg
Total width	0.76 m
Total height	1.98 m
Total length	1.16 m
Driving speed	Lowered 3 km/h, raised 1 km/h
Power source	2 pcs 12V batteries, 80Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Automatic
Height of railing	1.1 m
Height of skirting board	0.16 m



MoveAround
MA50-R

The MA50-R is a special variant of the MA50. The same features, but the MA50-R also has a retractable basket that allows you to get up into 60x60 false ceilings.

SPECIFICATIONS

Size of the platform	0.56 m x 0.52 m
Total load on the platform	Max 180 kg
Total number of people	Max 1
Working height	5 m
Platform height	3 m
Lifting time (180 kg)	16 s
Weight	343 kg
Total width	0.76 m
Total height	1.66 m
Total length	1.16 m
Driving speed	Lowered 4 km/h, raised 2 km/h
Power source	2 pcs 12V batteries, 80Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Automatic
Height of railing	1.1 m
Height of skirting board	0.15 m

5M
WORKING HEIGHT

180KG
MAX LOAD

343KG
WEIGHT





5M
WORKING HEIGHT

LIFTING TABLE

Width 0.65 m
Length 0.44 m
Max load 50 kg

180KG
MAX LOAD

386KG
WEIGHT



StockPicker
SP50

Driveable lift with height-adjustable lifting table. 5 meters working height and lifting table capacity of 50 kg. Suitable for shops and warehouses.

SPECIFICATIONS

Size of the platform	0.53 m × 0.64 m
Total load on the platform	Max 180 kg (incl. lifting table)
Total number of people	Max 1
Working height	5 m
Platform height	3 m
Lifting time (180 kg)	16 s
Weight	386 kg
Total width	0.76 m
Total height	1.73 m
Total length	1.48 m
Driving speed	Lowered 4 km/h, raised 2 km/h
Power source	2 pcs 12V batteries, 110Ah (C20), maintenance-free
Line voltage	24V
Battery charger	230V, 50 Hz / 60 Hz
Lifting system	Single manoeuvred hydraulic cylinder
Wheels	ø 200 mm, polyurethane coating, leaves no marks
Parking brakes	Automatic
Height of railing	1.1 m
Height of skirting board	0.15 m

ADVANTAGES OF SAFELIFT



Decoupling

The drive is disconnected with a simple grip and the lift is manually moved. (Applies to MA50, MA60, MA50-R & SP50)



Compact

Compact design for easy passage in tight spaces.



Low dead weight

Low dead weight enables transport in ordinary lifts and on sensitive floors.




User friendly

Developed with a focus on user-friendliness & ergonomics.



USB socket

USB sockets are available for easy charging of tablet or mobile device. (Applies to PA50, PA60, MA50, MA50-R & MA60)



Small turning radius


With a small turning radius of 1.2 m, the lift easily takes the corner.



**SAFE AND EFFICIENT
WORK AT HEIGHT**

SAFELIFT®

SAFELIFT[®]

 Made in Sweden

Safelift is manufactured and marketed by:

Address: Låglyftar i Sverige AB
Kvarnvägen 14
SE-352 41 Växjö
Sweden

Website: www.safelift.se

E-mail: info@safelift.se